

MAJESTIC PUMPS



Applications: Super-quiet pump (1,450 rpm). High volume self-priming pump available in 1,450 rpm and 2,850 rpm versions, ideal for large filtration systems.

Features: • Large suction-side pre-filter together with excellent hydraulic performance ensures high filtration capacity.

Filter with poly carbonate lid for easy viewing of pre-filter basket.

Standard connection flanges together with broad base make the system robust and durable.

Counter-flanges not supplied as standard equipment but available on request.

Turbine available in noryl or marine bronze (customer's choice).

Ideal for sea water conditions, fitted with AISI-316 mechanical seal (available on request).

Material of Construction: Pre-filter body, pump body, volute, pump base and cover in glass-fibre loaded polypropylene resistant to pool chemicals. Pre-filter basket in polythene, poly carbonate pre-filter cover with four-pin closure system, noryl impeller. Mechanical seal in ceramic carbon and AISI-304 stainless steel. Screws in AISI-304 stainless steel. Shaft in AISI-316 stainless steel.

Type	HP	KW	R.P.M.	Height w.c.m.										Dia	
				6	8	10	12	14	16	18	20	22	24	ASP.	IMP
				Flow - m³/h											
IM - 4-300	3.0	2.2	1,450	63	53	43	30	16						110	110
IM - 4-400	4.0	3.0	1,450	72	64	56	46	35	20					110	110
IM - 4-550	5.5	4.0	1,450	115	96	79	52	20						110	110
IM - 4-750	7.5	5.5	1,450	136	121	101	83	59	h26					110	110
IM - 4-1000	10.0	7.5	1,450	156	146	126	108	88	61	30				110	110
IM - 2-1250	12.5	9.2	2,850	191	182	165	146	132	115	102	76	43		110	110
IM - 2-1500	15.0	11.0	2,850	203	194	181	171	158	145	130	120	100	80	110	110